

DFWDXT

"DFWDXT": INDICATOR WITH LARGE AND VERY BRIGHT RED LED DISPLAY



Digital weight indicator, with large and very bright and efficient, 40 mm red LED matrix display (SMD technology), easily visible from all angles, from long distances, and in full sunlight. Brightness intensity is easily adjustable through the software on PC. Its high performance and available programmes make it suitable for all industrial and commercial applications. CE-M approvable (OIML R-76 / EN 45501).

**The best solution
for advanced industrial
applications**

MAIN STANDARD FEATURES

- Waterproof 5-key functional keypad.
- 6 large and very bright 40 mm LED digits, easily visible from all angles and from great distances, with an adjustable brightness intensity.
The SMD technology guarantees a high efficiency and brightness, also in full sunlight.
- 6 LED for indication of active functions.
- Stainless steel case with IP68 protection against rain and dust, easy to clean and resistant in harsh and corrosive environments.
- Suitable for use on the table, or wall.
- Dimensions 264x174x115mm.
- Up to 10.000e or multirange 3 x 3000e @ 0,3 μ V/e in CE-M approved version for legal for trade use.
- Up to 1.000.000 displayable divisions with internal resolution up to 3.000.000 points.
- Up to 8 signal linearization points.
- A/D 24-bit sigma-delta conversion, up to 200 conv./sec. autoselect.
- Digital calibration and set-up from keyboard or from PC with DINITOOLS™.
- Power supply 110-240Vac or 6 Vdc through fitted built-in rechargeable battery.
- Connection with up to 8 load cells with 350 Ohm input resistance.

MAIN CERTIFICATIONS

- EU Type Examination Certificate (45501:2015)
- OIML R76

FUNCTIONS

- KEYBOARD:
Zeroing, Automatic tare, Presetable tare, printing and/or data transmission, selectable function command, on/off switching.
- SELECTABLE FUNCTIONS:
 - High Resolution Weighing x 10.
 - Net/Gross or lb/kg conversion.
 - Accumulation.
 - Formula weighing.
 - +/- Checkweighing.
 - Percentage weighing.
 - Approved transmission of the weight to PC/PLC or data recording on MMC/USB (with Alibi memory ALMEM option).
 - Counting(Max. resolution of 1.500.000 divisions).
 - In/Out Truck weighing.
 - Hold and Peak.
 - Set Point Control (with DFIO option).

AVAILABLE FUNCTIONS FROM REMOTE CONTROL

- Infrared 19-key remote control: zero, tare / manual tare, enable / disable function, print, switch-off.
- Radiofrequency 6-key remote control: zero, tare, enable / disable function, print, switch-off.



“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

**DINI ARGEO
FRANCE sarl**
France

**DINI ARGEO
GMBH**
Germany

**DINI ARGEO
UK Ltd**
United Kingdom

**DINI ARGEO WEIGHING
INSTRUMENTS Ltd**
China

**DINI ARGEO
OCEANIA**
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE