

TPRXT

"TPRXT": ATTACHED THERMAL PRINTER WITH IP65 PROTECTION.



Thermal printer with IP65 stainless steel case and protection shutter door against water sprays and dust. Particularly suitable for the chemical and foodstuff industry, as well as in applications in harsh or strict hygiene environments. Mounted attached to the "XT" weight indicators, with a STAINLESS STEEL case.

The best solution for advanced industrial applications

TECHNICAL SPECIFICATIONS

• PRINT METHOD: Thermal.

• RESOLUTION: 203 dpi.

• COLUMNS: 24/40.

• PAPER WIDTH: 58 mm.

• ROLL SIZE: Diameter of 50 mm.

• PRINT SPEED: up to 50 mm/sec.

• PRINT FORMATS: Normal, double height and width, negative, underlined, expanded.

• PRINT DIRECTION: selectable (straight or upside down).

• PROGRAMMABLE FEATURES: Baud rate, data length, parity bit, handshaking, autofeed, number of columns, font size and print density.

N.B. ACCESSORY WHICH MAY BE ORDERED ONLY TOGETHER WITH A SUITABLE WEIGHT INDICATOR.





DINI ARGEO FRANCE sarl France DINI ARGEO GMBH Germany

DINI ARGEO UK Ltd United Kingdom DINI ARGEO WEIGHING INSTRUMENTS Ltd China DINI ARGEO OCEANIA Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20 41042 Spezzano di Fiorano Modena - Italy Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15 41042 Spezzano di Fiorano Modena - Italy Tel. +39.0536 921784

-	
	SALES AND TECHNICAL ASSISTANCE SERVICE