

# BLUETOOTH

## BLUETOOTH INTERFACE FOR WEIGHT INDICATORS



Thanks to the Bluetooth interface, the exchange of data between the digital scales and the computer system will be simpler and quicker: it is sufficient to be at a few meters from the weight indicator in order to update the databases, read the memory, transmit commands, receive data, check the configuration, etc.

**The best solution  
for advanced industrial  
applications**

## BLUETOOTH INTERFACE: FEATURES

- BLTH-2 MODEL:
  - Standard: Bluetooth "version 3.0"
  - Class: 2
  - Identifying code of the programmable device
  - Maximum working distance: 10m
  - Transmission speed: 560kbps
  - Supported Bluetooth profiles: Serial Port Profile (SPP)
  - Antenna: integrated on the board, internal
  - Installation: integrated inside the weight indicator

NOTE: BLTH is an option to be specified when ordering the digital scale or the weight indicator.

## SET OF COMMANDS AND COMMUNICATION PROTOCOLS

- The Dini Argeo weight indicators are fitted with a communication protocol for the data exchange, which allows the weight reading, the execution of the main scale functions and the programming of the databases (depending on the indicator model).

### DETAIL 1



Evolved version for specific applications.



“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

**DINI ARGEO  
FRANCE sarl**  
France

**DINI ARGEO  
GMBH**  
Germany

**DINI ARGEO  
UK Ltd**  
United Kingdom

**DINI ARGEO WEIGHING  
INSTRUMENTS Ltd**  
China

**DINI ARGEO  
OCEANIA**  
Australia



**COMPANY HEADQUARTERS**

Via Della Fisica, 20  
41042 Spezzano di Fiorano Modena • Italy  
Tel. +39.0536 843418

**SERVICE ASSISTANCE**

Via Dell'Elettronica, 15  
41042 Spezzano di Fiorano Modena • Italy  
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE