

OBRF3GD

"OBRF3GD": RADIO FREQUENCY INTERFACE BOX FOR ATEX 2 and 22 ZONES



Radio frequency module for the wireless data communication in ATEX 2 and 22 zones, with protection methods according to:
ATEX II 3G Ex nA IIC T6 Gc X for gases
ATEX II 3D Ex tc IIIC T85°C Dc IP66 X for dust.
It can be applied to both bench/floor scales as well as mobile scales, such as pallet truck scales or pallet weighing scales, and it allows to transmit data at a very long distance.

**The best solution
for advanced industrial
applications**

Technical features

- IP66 ABS case.
- Dimensions case (lxwxh): 120x80x55mm.
- Fitted with 3m shielded cable, for connection to the indicator.
- Power supply directly from the indicator.

Operating features

- Work frequency from 868 to 870 MHz, which reduces the risk of interferences with the classic radio frequency systems.
- Up to 50 different channels, easily programmable with the programme on PC, in order to install various independent systems in the same work area.
- Max. functioning distance, in appropriate environmental and installation conditions: up to 70m indoors, and up to 150m outdoors.
- Does not require particular communication protocols, transmission in transparent manner of any character received in input.



“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE