

# DAC160

## "DAC160": 16 BIT ANALOGUE PROGRAMMABLE OUTPUT



16 bit analogue output, in voltage or in current. Programmable as 0...5/0...10Vdc, 0...20/4...20mA through the **indicator** or through the PC with Dinitools. Particularly suitable for use with PLC's and in industrial environments.

The best solution for advanced industrial applications

## **TECHNICAL FEATURES:**

- Output values programmable through the indicator or through the PC Dinitools: 0...5/0...10Vdc or 0...20/4...20mA.
- 16 bit resolution (65536 divisions).
- Update frequency: from 30 to 50Hz (depending on the weight indicator).
- Precision: minimum +/- 0.08%, typical 0.015% in relation to the F.S.O. of the analogue output (operating temperature 25°C).
- Maximum applicable resistance on the output in current: 300 ohm.
- Minimum applicable resistance on the output in voltage: 1 Kohm.
- Easily configurable through the indicator or through the PC using Dinitools.





DINI ARGEO FRANCE sarl France DINI ARGEO GMBH Germany

DINI ARGEO UK Ltd United Kingdom DINI ARGEO WEIGHING INSTRUMENTS Ltd China DINI ARGEO OCEANIA Australia



#### **COMPANY HEADQUARTERS**

Via Della Fisica, 20 41042 Spezzano di Fiorano Modena - Italy Tel. +39.0536 843418

#### SERVICE ASSISTANCE

Via Dell'Elettronica, 15 41042 Spezzano di Fiorano Modena - Italy Tel. +39.0536 921784

-	
	SALES AND TECHNICAL ASSISTANCE SERVICE