

JBQI

"JBQI": EQUALISED JUNCTION BOX WITH 4/6 INPUTS, IN IP65 STAINLESS STEEL



Stainless steel junction box with IP65 protection from water and dust, and fitted with electronic board for junction and equalisation of 4 or 6 load cells. Terminal board with screw for easing the connection of the load cells and the signal adjustment trimmer, for an accurate and reliable equalisation.

TECHNICAL FEATURES

- Stainless steel case.
- Protection degree: IP65.
- Maximum input voltage: 24Vdc.
- Maximum input current: 700mA.
- Maximum input load cell signal: 1000mV.
- Temperature effect: 50ppm/°C.
- Protection diodes against surcharges or electrostatic discharges.
- 4 cell inputs on screw connector or on soldering squares (for JB4Q1 model).
- 6 cell inputs on screw connector or on soldering squares (for JB6QI model).
- Dimensions: 155x158x45mm (lxwxh) for JB4QI
- Dimensions: 190x132x50mm (lxwxh) for JB6QI

DETAIL 1



JB6Q1: Junction and equalisation box, in IP65 stainless steel.





DINI ARGEO FRANCE sarl France DINI ARGEO GMBH Germany

DINI ARGEO UK Ltd United Kingdom DINI ARGEO WEIGHING INSTRUMENTS Ltd China DINI ARGEO OCEANIA Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20 41042 Spezzano di Fiorano Modena - Italy Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15 41042 Spezzano di Fiorano Modena - Italy Tel. +39.0536 921784

-	
	SALES AND TECHNICAL ASSISTANCE SERVICE