

LCCB

"LCCB": CABLE for CONNECTION TO LOAD CELLS



Shielded cable for connection of weight indicators to load cells or junction boxes.

**The best solution
for advanced industrial
applications**

LCCB cable features

- Type: 6 x 0,25 mm².
- Built-in shielding for protection from disturbances.

<u>Dini Argeo standard of colour codes</u>	
<i>Colour</i>	<i>Function</i>
YELLOW	OUTPUT -
PINK	OUTPUT +
GREEN	SENSE +
WHITE	SENSE -
BROWN	INPUT +
GREY	INPUT -

LCCBM cable features

- Indicated for applications with moving cables.
- Type: 4 x 0,34 mm².
- Built-in shielding for protection from disturbances.

<u>Dini Argeo standard of colour codes</u>	
<i>Colour</i>	<i>Function</i>
YELLOW	OUTPUT -
GREEN	OUTPUT +
WHITE	INPUT -
BROWN	INPUT +

DETAIL 1



LCCBM: shielded 4-pole cable for load cells.



“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784



SALES AND TECHNICAL ASSISTANCE SERVICE